










Specifications

| | |
|---------------------------------|--|
| » Fingerprint Users | 1,000 |
| » Card User | 1,000 |
| » Password User | 1,000 |
| » Attendance Records | 100,000 |
| » Fingerprint Verification Mode | 1:1, 1:N |
| » Working Mode | Offline |
| » Verification | Fingerprint, ID Card, Password |
| » Combination | FP + Card, PIN + Card, FP + PIN + Card |
| » Verification Time | > 1.0s |
| » False Rejection Rate | < 0.01% |
| » False Acceptance Rate | < 0.0001% |
| » Finger Print Sensor | Optical Sensor |
| » Screen | 2.8 inches (Color Display) |
| » Display Language | English |
| » Communication | RS485, USB Drive/Link, TCP/IP |
| » Working Humidity | 20%-60% |
| » Working Temperature | 0°C-50°C |
| » Power Supply | 9V DC |
| » Idle Current | 400mA |
| » Working Current | 500mA |
| » Sound Indicator | Buzzer, Voice |
| » Access Control | Built-in |



Features

| | | | |
|---|---|---|---|
|  |  |  |  |
| Fingerprint | RF Card | Personal Identity Number | USB Link |
|  |  |  | |
| Access Control | TCP/IP | USB Disk | |