



EM Lock to Connect



ST 25 to Connect



**Specifications**



- » Fingerprint Users 3,000/5,000
- » Card User 3,000/5,000
- » Password User 3,000/5,000
- » Attendance Records 100,000
- » Fingerprint Verification Mode 1:1, 1:N
- » Working Mode Offline/Online
- » Verification Fingerprint, ID Card, Password
- » Combination FP + Card, PIN + Card, FP + PIN + Card
- » Verification Time > 1.0s
- » False Rejection Rate < 0.01%
- » False Acceptance Rate < 0.0001%
- » Fingerprint Sensor Optical Sensor
- » Screen 3 inches (Color Display)
- » Display Language English
- » Communication RS485, USB Drive/Link, TCP/IP
- » Working Humidity 20%-60%
- » Working Temperature 0°C-50°C
- » Power Supply 12V DC
- » Idle Current 400mA
- » Working Current 500mA
- » Sound Indicator Buzzer, Voice
- » Access Control Built-in
- » Access control Directly control of door lock / Indirectly control of door lock via Wiegand access controller.  
Support 50 access time zones, combination identification, anti-pass back.
- » Battery Backup Optional
- » Server Connection Auto Push Technology

Auto Adapt Sensor

Auto Push Technology



**Features**

-   
USB Link
-   
Personal Identity Number
-   
Access Control
-   
TCP/IP
-   
EM Card
-   
USB Disk
-   
RS232/485